

01.01.2023



# **Coated 80 FSC**

# **Permanent**

#### **Face material**

Label material Coated 80 FSC permanent

Raw material 1902063

Product Glossy white coated woodfree paper. The product is FSC<sup>TM</sup> - certified. FSC

certification ensures that products are made from responsibly managed forests.

#### **Typical technical values**

#### **Adhesive**

Adhesive Permanent

Type General purpose permanent acrylic water based adhesive. Good adhesion to a

wide variety of substrates, including non-polar surfaces.

General characteristics Suitable for direct food contact with dry and moist, non-fatty food.

#### **Typical technical values**

Tack 11 N/mm FTM 9

min. labelling temperat. 0 °C Usage temperature -20° to +70° C

Peel Value 10 (N/25mm) 24h FTM2

# **Backing paper**

Backing YG60

Product Honey supercalandered glassine paper, one side siliconized. There may be slight

variations in tone.

#### **Typical technical values**

 $\begin{array}{ccccc} \text{Grammage} & 56 & \text{g/m}^2 & \text{ISO 536} \\ \text{Thickness} & 49 & \mu\text{m} & \text{ISO 534} \\ \end{array}$ 



# **Additional information**

Not recommended for labelling curved surfaces with small diameters.

# **Use & application**

Multipurpose labels for industrial use, food, retail as well as transports and logistics. Testing for suitability between media, printers and inks is always recommended prior to use.

# **Printing**

Suitable for printing in Flexography, Offset, Screen, hot-foil and thermal transfer.

# Shelf life

12 months under storage conditions as defined by FINAT section 2.5 (20-25° C, 40-50% RH). Prolonged storage at higher temperatures and / or humidity levels will shorten the shelf life of the product.



#### Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to Carl Valentin's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.



Carl Valentin GmbH

Neckarstraße 78 – 86 u. 94

78056 Villingen-Schwenningen

Phone + 49 7720 9712 - 0 . Fax + 49 7720 9712 – 9901 info@carl-valentin.de www.carl-valentin.de

