

01.01.2023



Transfer Special Gold

Permanent

Characteristics Label

Label material	Transfer Special Gold permanent
Raw material	1903029
Adhesive bond	Rolls
Product	One side metallic coated, woodfree paper.
Use	Designed for promotional label application

Typical technical values

Substance	76	g/m ²	ISO 536
Caliper	63	µm	ISO 534
Gloss	60	%	Hunter 75°

Printability	Suitable for offset and flexography. UV-inks and inks for filmic materials are recommended
---------------------	--

Characteristics Adhesive

Adhesive	Permanent
Type	Permanent adhesive
Composition	Acrylic, waterborne
Use	Designed for permanent wine & spirits applications. Provides good adhesion to polar surfaces, tolerating fluctuations in temperature and humidity on the bottling line and during bottle storage. Also has good water-resistance during immersion in ice buckets. The stiffness of the label affects mandrel performance.

Typical technical values

Tack	15	N/25mm FTM 9
Labeling temp. min.	5	°C
Service temp. min.	-20	°C
Service temp. max.	80	°C

Additional info	Not suitable for applications where wash-off performance is needed. Formulation contains natural rubber latex.
------------------------	--

Characteristics Glassine

Backing	WHITE GLASSINE 85-FSC
Product	White glassine woodfree backing paper.
Use	For reelstock laminates, wine and spirit applications.

Typical technical values

Substance	78	g/m ²	ISO 536
Caliper	68	µm	ISO 534
Tensile strength MD	7.5	kN/m	ISO 1924
Tensile strength CD	3.2	kN/m	ISO 1924
Transparency	40	%	DIN 53147

Shelf life	From date of manufacture: 12 months, under FINAT defined storage conditions (+20-25° C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.
-------------------	---

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to Carl Valentin's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.



Carl Valentin GmbH
Neckarstraße 78 – 86 u. 94
78056 Villingen-Schwenningen
Phone + 49 7720 9712 - 0 . Fax + 49 7720 9712 – 9901
info@carl-valentin.de www.carl-valentin.de

